



## TS1522 Wireless LED Display with PA Speaker

The TS1522 is a unique wireless alphanumeric LED display that comes with a built-in Public Address speaker to provide easy time, voice and data messaging to accommodate a wide variety of application environments. Each TS1522 wireless unit is assigned a unique ID code to receive its own addressable messages. The TS1522 can also be assigned additional codes to receive group voice and alphanumeric messages with other PA speakers and LED displays.



### Specifications:

<b>Dimensions:</b>	26.5"L x 6.7"H x 2.5"D	<b>LED size &amp; color:</b>	2.5" or 5.0" Red
<b>Weight:</b>	6.50 lb.	<b>Frequency:</b>	148-174Mhz, 400-470MHz
<b>Power:</b>	120VAC, 60Hz 30-Watt 5V / 6A Power Adaptor	<b>Paging format:</b>	POCSAG, Narrow band
<b>Operating Temperature:</b>	32° to 120°F	<b>Data Baud rate:</b>	512 or 1200 BPS
<b>Humidity:</b>	0%-95% Non-condensing	<b>Receiver Sensitivity:</b>	10uV/M
<b>Frame and lens:</b>	Black metal frame with clear acrylic lens	<b>Channel spacing:</b>	12.5KHz
<b>Viewing distance:</b>	Up to 100 feet	<b>Audio power:</b>	20 Watt
<b>Data format:</b>	Two lines - 12 characters each or one double-sized line	<b>PA Capabilities:</b>	Live voice or eight (8) internal pre-programmed tone alerts and voice prompts
		<b>Paging addresses:</b>	Six capcodes
		<b>Limited Warranty:</b>	One-year Parts and Labor